



# 5000 PLUS

## DESCRIPTION

The 5000 Plus is similar to the standard 5000 but with the added feature of a vibrating feeder. This addition is hydraulically driven and operated by the remote-control handset.

Instant hydraulic adjustable jaws allow output product sizes to range from 20mm up to 100mm. Being only 1665mm wide, the 5000 Plus can enter sites where access and space are restricted. Dust suppression is fitted as standard, by means of fine water spray nozzles utilising standard domestic hose pressure.

The 5000 Plus makes light work of reinforced concrete, brick, porcelain and other aggregate type products. Crushing with the 5000 Plus can save thousands of pounds on muck away and bought in backfill. Using the wireless remote-control system crushing with a series can be a one-man operation.

## STANDARD FEATURES

Jaw aperture of 500mm x 250mm

Average product size 20mm to 100mm

Kubota 25HP 4- cylinder water cooled diesel engine Stage V emission compliant

Wireless remote-control system for all functions

## DIMENSIONS

Length 5600mm

Width 1665mm

Loading Height 2080mm

Weight 3170kg



+44 (0)1476 590790  [www.redrhinocrushers.co.uk](http://www.redrhinocrushers.co.uk)

 [sales@redrhinocrushers.net](mailto:sales@redrhinocrushers.net)